

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : Schluter®-SET White

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Tile adhesive

1.3. Details of the supplier of the safety data sheet

Schluter Systems L.P.
 USA: Schluter Systems L.P. | 194 Pleasant Ridge Road
 CAN: Schluter Systems (Canada) Inc. | 21100 chemin Ste-Marie
 Plattsburgh, NY | Ste-Anne-de-Bellevue, QC
 USA: schluter.com / CAN: schluter.ca

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Serious eye damage/eye irritation Category 2A H319
 Carcinogenicity Category 1A H350
 Specific target organ toxicity (single exposure) Category 3 H335
 Specific target organ toxicity (repeated exposure) Category 2 H373

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H319 - Causes serious eye irritation
 H335 - May cause respiratory irritation
 H350 - May cause cancer (Inhalation, oral)
 H373 - May cause damage to organs (central nervous system, respiratory system/digestive system) through prolonged or repeated exposure (Inhalation, oral)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P260 - Do not breathe fume, dust, spray, vapors
 P261 - Avoid breathing fume, spray, vapors
 P264 - Wash hands, forearms and face thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear protective clothing, protective gloves, face protection
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P312 - Call a doctor if you feel unwell
 P314 - Get medical advice/attention if you feel unwell
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P403+P233 - Store in a well-ventilated place. Keep container tightly closed
 P405 - Store locked up
 P501 - Dispose of contents/container to in accordance with local/regional/international regulations

2.3. Other hazards

No additional information available

Schluter®-SET White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Quartz	(CAS No) 14808-60-7	60 - 75	Eye Irrit. 2A, H319 Carc. 1A, H350 STOT SE 3, H335 STOT RE 2, H373
Calcium Oxide	(CAS No) 1305-78-8	1-5	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Trade Secret	(N/A)	1-5	Eye Irrit. 2A, H319
Chromium (VI) compounds, with the exception of barium chromate and of compounds specified elsewhere in this Annex	(CAS No) 18540-29-9	0-0.01	Skin Sens. 1, H317 Carc. 1A, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16
Specific chemical identity and exact percentages are withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after eye contact : Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

Schluter®-SET White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Wear personal protective equipment. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ A2
ACGIH	Remark (ACGIH)	Lung Cancer; Silicosis
OSHA	OSHA PEL (TWA) (mg/m ³)	50 µg/m ³
OSHA	Remark (OSHA)	(3) See Table Z-3.
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ Ca
NIOSH	Remark (NIOSH)	See Appendix A
Portland Cement (65997-15-1)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
ACGIH	Remark (ACGIH)	Pulm func; resp symptoms; asthma
Limestone (1317-65-3)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³ Total dust
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ Respirable dust
Calcium Oxide (1305-78-8)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³
ACGIH	Remark (ACGIH)	URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
IDLH	US IDLH (mg/m ³)	25 mg/m ³
Chromium (VI) compounds, with the exception of barium chromate and of compounds specified elsewhere in this Annex (18540-29-9)		
ACGIH	ACGIH TWA (mg/m ³)	0.01 mg/m ³ (as Cr)
OSHA	OSHA PEL (TWA) (mg/m ³)	0.005 mg/m ³ (See Appendix C of the NIOSH Pocket Guide to Chemical Hazards)
IDLH	US IDLH (mg/m ³)	15 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.001 mg/m ³ (8 hour) See Appendix A/C of the NIOSH Pocket Guide to Chemical Hazards
Particulates Not Otherwise Regulated (Total Dust)		
ACGIH	ACGIH TWA (mg/m ³)	TWA: 3 mg/m ³ 8 hours. Form: Respirable TWA: 10 mg/m ³ 8 hours. Form: Total dust
OSHA	OSHA PEL (TWA) (mg/m ³)	TWA: 5mg/m ³ 8 hours. Form: Respirable TWA: 15 mg/m ³ 8 hours. Form: Total dust

Schluter®-SET White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves.
Eye protection	: Safety glasses.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Wear respiratory protection.
Environmental exposure controls	: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Color	: Powder : Grey or white
Odor	: Odorless.
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: Not applicable
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Schluter®-SET White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation, oral).

Quartz (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Chromium (VI) compounds, with the exception of barium chromate and of compounds specified elsewhere in this Annex (18540-29-9)

IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.
Specific target organ toxicity – repeated exposure	: May cause damage to organs (central nervous system, respiratory system/digestive system) through prolonged or repeated exposure (Inhalation, oral).
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after eye contact	: Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
GWPmix comment	: No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
-------------------------	---

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

Schluter®-SET White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Quartz (14808-60-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Portland Cement (65997-15-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Limestone (1317-65-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Calcium Oxide (1305-78-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Chromium (VI) compounds, with the exception of bariumchromate and of compounds specified elsewhere in this Annex (18540-29-9)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Quartz (14808-60-7)

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Portland Cement (65997-15-1)

WHMIS Classification Class E - Corrosive Material

EU-Regulations

No additional information available

National regulations

Quartz (14808-60-7)

Listed on IARC (International Agency for Research on Cancer)

Chromium (VI) compounds, with the exception of bariumchromate and of compounds specified elsewhere in this Annex (18540-29-9)

Listed on IARC (International Agency for Research on Cancer)

Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

Quartz (14808-60-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

Quartz (14808-60-7)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List

Portland Cement (65997-15-1)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List

Limestone (1317-65-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

Calcium Oxide (1305-78-8)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

SECTION 16: Other information

Revision date : 02/27/2017

Schluter®-SET White

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : ECHA - [http://apps.echa.europa.eu/registered/data/dossiers/DISS-9d9b1369-7454-687c-e044-00144f67d249/DISS-9d9b1369-7454-687c-e044-00144f67d249.html](http://apps.echa.europa.eu/registered/data/dossiers/DISS-9d9b1369-7454-687c-e044-00144f67d249/DISS-9d9b1369-7454-687c-e044-00144f67d249_DISS-9d9b1369-7454-687c-e044-00144f67d249.html); GESTIS - [http://gestis-en.itrust.de/nxt/gateway.dll/gestis_en/000000.xml?f=templates\\$fn=default.htm\\$3.0](http://gestis-en.itrust.de/nxt/gateway.dll/gestis_en/000000.xml?f=templates$fn=default.htm$3.0); ChemIDPlus - <http://chem.sis.nlm.nih.gov/chemidplus/rn/100-51-6>; Sciencelab.com, Inc. MSDS dated May 21, 2013. GESTIS DNEL Database [[http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates\\$fn=default.htm\\$vid=dneleng:ddb eng\\$3.0](http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates$fn=default.htm$vid=dneleng:ddb eng$3.0)].


Full text of H-phrases:

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



HMS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product